

interior/exterior multi-purpose primer **829 LINE**

American Pride® paints are high performance coatings which are low in odor during application and drying. These products are ideal for use in occupied areas because of their low odor and VOCs (Volatile Organic Compounds).

RECOMMENDED USE

American Pride® Multi-Purpose Primer is a premium quality, 100% acrylic primer that is formulated to provide outstanding coverage, adhesion, mold and mildew resistance, blister resistance, and stain blocking over a variety of interior and exterior surfaces. This product has excellent flow and leveling with minimal odor. Interior Surfaces: New or Previously Painted Wood, Plywood, Ceiling Tile, Formica®, Masonite®, Ceramic Tile and Cured Plaster. Also suitable as a sealer and primer for use under new wall coverings and can be used as a primer coat over existing wall coverings. Exterior Surfaces: New or Previously Painted Wood, Aluminum Siding, Hardboard Siding, Shingles, Shakes, Concrete, Masonry and Brick.

SURFACE PREPARATION

Clean all surfaces to be painted and remove all dirt, grease, oil, fingerprints, mildew, waxes, etc. Rinse and allow the surface to dry. Remove all loose or peeling paint and any deteriorated substrate. Reattach or remove any loose wall covering. Glossy surfaces should be dulled by sanding. Fill in any holes or cracks with an appropriate patching material and sand again as necessary. Remove all dust and seal the surface with this primer. Knot holes and water stains should be spot primed before priming the entire surface.

EQUIPMENT

Conv. Spray:	40 PSI TIP:704/FX
Airless Spray:	1800 - 2400 PSI TIP:.015" - .021"
Brush:	Polyester or Nylon
Roller:	3/8" - 1/2" Nap Cover
Pad:	Standard

**VOC level as determined on untinted paint within the precision of ASTM D 3960*

THINNER & CLEAN-UP

Thinning is not recommended, but if necessary, use clean water sparingly. Soap and water clean-up.

LIMITATIONS

- Do not apply when air, surface, or product temperature is below 50°F (10°C) or if temperature might drop to this level within 4 hours of application.
- Do not apply in temperatures above 90°F (32°C).

PACKAGING

Quarts, Gallons, 5 Gallons

COLORS

Tintable White

Note: Can be tinted with up to 5 oz. of colorant.

SPECIFICATION DATA

Type:	100% Acrylic Latex
Finish:	Flat
» Sheen:	5 Max @ 85°
% Solids (varies with color):	
» By Weight:	57 ±2%
» By Volume:	38 ±2%
Wt./Gallon: (White only):	11.84 lbs.
Flashpoint:	212°F (PMCC)
VOC lbs./gal (max):	< 0
VOC grm/ltr (max):	< 0
Thinner:	Water
Clean-up:	Soap and Water
Dry Time:	
» To Touch:	2 hours
» To Recoat:	4-8 hours
» To Service:	Overnight
Thickness:	
» Dry:	1.5 mil
» Wet:	4.0 mil
Coverage:	300-400 sq. ft./gal (on smooth surfaces)
Flame Spread Rate:	Class A (0-25 on non-combustible surfaces)